



Pro1
Model #

7D 7 Day Programmable
5/1/1 5/1/1 Programmable
NP Non-programmable

Stages of Heat
 Stages of Cool
 Gas, Electric or Oil
 Heat Pump
 Millivolt
 Battery Power
 24V Power (Hardware)
 Dual Fuel Compatible
 Display Size (Square Inches)
 Auto Changeover
 Filter Change Reminder
 Room Temperature Calibration
 Minimum Compressor Run Time
 Compressor Short Cycle Delay
 Adjustable Heating Temperature Swing
 Adjustable Cooling Temperature Swing
 Programmable Fan
 Keypad Lockout
 Adjustable Setpoint Limits
 Memory Type (Permanent)
 Energy Star
 Warranty (Years)

Terminals

Pro1 Model #	7D	5/1/1	NP	Stages of Heat	Stages of Cool	Gas, Electric or Oil	Heat Pump	Millivolt	Battery Power	24V Power (Hardware)	Dual Fuel Compatible	Display Size (Square Inches)	Auto Changeover	Filter Change Reminder	Room Temperature Calibration	Minimum Compressor Run Time	Compressor Short Cycle Delay	Adjustable Heating Temperature Swing	Adjustable Cooling Temperature Swing	Programmable Fan	Keypad Lockout	Adjustable Setpoint Limits	Memory Type (Permanent)	Energy Star	Warranty (Years)	Terminals	
Wireless																											
T955W**	7D	5/1/1	NP	3*	2	•	•	•	•	H	13	•	•	•	•	•	•	•	•	•	•	•	•	•	5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O	
Wired																											
T925	7D	5/1/1	NP	3	2	•	•	•	•	S	13	•	•	•	•	•	•	•	•	•	•	•	•	•	5	R, C, Y, Y2, W2, E, G, B, O	
T915	7D	5/1/1	NP	2	2	•	•	•	•		13	•	•	•	•	•	•	•	•	•	•	•	•	•	5	R, C, Y, Y2, W, W2, G, B, O	
T905	7D	5/1/1	NP	1	1	•	•	•	•		13	•	•	•	•	•	•	•	•	•	•	•	•	•	5	Rh, Rc, C, Y, W, G, B, O	
BETTER																											
T855	7D	5/1/1	NP	3*	2	•	•	•	•	S	8	•	•	•	•	•	•	•	•	•	•	•	•	•	5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O	
T805	7D	5/1/1	NP	1	1	•	•	•	•		8	•	•	•	•	•	•	•	•	•	•	•	•	•	5	Rh, Rc, C, Y, W, G, B, O	
T801			NP	1	1	•	•	•	•		8	•	•	•	•	•	•	•	•	•	•	•	•	•	5	Rh, Rc, C, Y, W, G, B, O	
GOOD																											
T771			NP	0/1	0/1	•	•	•	•		4			•		•	•	•			•	•		5	R, C, W/Y, G		
T725			5/1/1	2	1	•	•	•	•	S	4		•	•	•	•	•	•				•	•	5	R, C, Y, W2, E, G, B, O		
T721			NP	2	1	•	•	•	•	S	4		•	•	•	•	•	•				•		5	R, C, Y, W2, E, G, B, O		
T715			5/1/1	2	2	•	•	•	•		4		•	•	•	•	•	•				•	•	5	R, C, Y, Y2, W, W2, G		
T705			5/1/1	1	1	•	•	•	•		4		•	•	•	•	•	•				•	•	5	Rh, Rc, C, Y, W, G, B, O		
T701			NP	1	1	•	•	•	•		4			•		•	•	•				•		5	Rh, Rc, C, Y, W, G, B, O		
T601			NP	1	1	•	•	•	•		.5						•	•				•		5	Rh, Rc, C, Y, W, G, B, O		



* 3 heat stages for heat pump or 2 heat stages for conventional.

** Wireless accessories available for T955W. R251W is an indoor remote temperature sensor. R250W is an outdoor remote temperature sensor.

H Dual fuel hardware balance point. Requires outdoor temperature accessory R250W.

S Dual fuel software setting. Y de-energizes when W2 energizes.